# **ProsKit**® User's Manual

# SS-595 Series Smoke Absorber

SS-595 Series Smoke Absorber is designed to absorb 80% of potentially harmful contaminants; and it can also use as a blow fan to decrease the temperature. The stepless air volume can be adjusted as per varying requirement. Nine adjustable angles allow users to adjust the absorber without any tool. It has two ways to place, desktop design or hang on to any stand. SS-595 new 23W brushless motor offers low noise and long life service. With activated carbon filter to absorb flux and lead smoke to protect user's health.

#### Safety Note

The appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.

Children should be supervised to ensure that they do not play with the appliance.


### Warning

If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.

Please make sure smoke absorber is disconnected with power supply before taking off the protective apparatus.

### Specification

Specification			
Item No.	SS-595A	SS-595B	SS-595H
Voltage & Watt	110-120V~	220-240V~	220-240V~
	60HZ	50HZ	50HZ
Power code	□ A type	B type	
	1.3M	1.3M	1.3M
Power consumption	8-23W (adjustable)		
Capacity	0.2~1m³/min(max) (adjustable)		
Dimension	220*220*145mm		
Weight	1,200g		
Accessories	Filter (1 PCE)		



### **Optional Accessories**

Activated-Carbon Filter

/ totivated Odibott i liter	
Item No	5SS-593-F
Size	130x130x10mm
Amount of activated-carbon filter	7g
Max. absorbing weight of noxious components per one filter	2g

# Operating Instruction

- 1. Install the activated carbon filter from botton.
- 2. Turn on the power switch.
- 3. Adjust the angle and wind volume as per requirement.
- 4. Reverse side can be used as a fan.

# Replacing the filter

Under normal operating conditions, the filter should be replaced since absorption capacity decline.

The filter may also need replacement when the dust adheres. (Never allow the filter to become wet.).



# SS-595 系列兩用吸煙器

SS-595 系列兩用吸煙機設計用於吸收 80%的潛在有害污染物或作為吹風器來降低物件溫度。備有九段不同角度可根據不同需求進行調整,同時可依工作場合配置放置於桌面或吊掛在支架上。無段風量可視吸煙或吹風需求進行調整。SS-595 新型 23W 無刷電機可提供低噪音、更長的使用壽命,採用活性炭海綿幫助過濾吸收助焊劑和鉛煙,以保護用戶的健康。

# 安全使用說明

※此吸煙設備適用於對該產品具有操作經驗的人員. 若缺乏經驗或身體 及精神能力不適者請避免使用,除非有其他人員協助指導或監督且為安全 的情况下,並依據操作手冊指示使用該設備。

※請避免孩童使用。

※開機前請確實檢查此吸煙器,確認配件是否完整,並確認電壓為要求的可使用範圍

### 送修警示要求

如果吸煙器損壞,為了避免危險,請退回寶工實業或其指定的服務代理商進行檢測與更換。

# 操作指南

操作前請先確實檢查

- 1. 檢查電源及插頭是否符合本產品要求之規格
- 2. 核對產品是否有配件缺少狀況
- 3. 機器內是否已裝入高效能活性碳海棉濾片
- 4. 確認電源範圍開機使用

#### 產品規格

產品型號.	SS-595A	SS-595B	SS-595H
電壓與電源	110-120V~ 60HZ	220-240V~ 50HZ	220-240V~ 50HZ
標準插頭	A type 1.3M	B type 1.3M	H type 1.3M
消耗功率	8-23W (可調整)		
吸煙容量	0.2~1m³/min(max) (可調整)		
本體尺寸	220*220*145mm		
本體重量	1,200g		
配件	活性碳海綿濾片 (1 片)		

### 選購配件: 活性碳海棉漬片

產品型號	5SS-593-F		
數量	1 片/包		
尺寸	130x130x10mm		
濾片總重量	7g		
每片最大吸煙總量	2g		



### 更換濾片

- 1. 由吸煙器底部將活性碳海綿濾片放入。
- 2. 打開開關。
- 3. 依需求調整吸煙/吹風角度及風量。
- 4. 轉到反面可作為吹風降溫使用。

# 過濾片更換時機

- 在正常操作條件下,吸煙能力會逐漸下降,活性碳海綿濾片應該定期更換。
- 當灰塵黏著於活性碳海綿上且呈現灰白色時,請更換活性碳海 綿濾片。



PROKIT'S INDUSTRIES CO., LTD

http://www.prokits.com.tw

Email: pk@mail.prokits.com.tw