


Nylon Cable Glands



Overview


- ◆ Material: made from UL Nylon 66, 94V-2 and tighten ring from rubber.
- ◆ Feature:
 - 1.Special design of clamp ring, good clamping strength and protective for electric machinery.
 - 2.No need of disassembling the cable gland, cable can go through directly then tighten it, easy to operate and save time.
- ◆ Application: used for machinery control box, distribution plate, machine and electrical, etc.



A
螺母
Lock nut



B
垫圈
Washer




C
本体
Body

E
夹紧爪
Claw



D
夹紧圈
Seal



F
迫紧头
Sealing nut

Technical Parameters

编号 Item NO.	D1(mm)	D2(mm)	L1(mm)	L2(mm)	L3(mm)	L4(mm)	B1(mm)	电缆直径范围 Cable range
PG-N07	12.6	8.5	8.4	5.5	13.4	12	6.6	3.5-6
PG-N09	15.5	11	8.5	5.5	15	13.5	8.8	4-8
PG-N011	18.3	13.4	8.5	5.5	17	15	10.8	5-10
PG-N13.5	20.5	15.4	8.5	5.5	18	15	12.8	6-12
PG-N16	23	17.9	10.5	6	18.5	16.5	14.8	10-14
PG-N19	24.5	19	11	6	20	19	16	12-15
PG-N21	28.5	23	10.8	6	20.7	20	18.9	13-18
PG-N24	32.5	27	11.8	7	24.2	22	22.8	15-22
PG-N29	36.6	29	11.4	7.5	26.1	24	25.8	18-25
PG-N36	47.8	39	15	7.5	31	28	33.8	22-32
PG-N42	55	46	13.2	8	33.8	30	39	30-38
PG-N48	60	52	14.2	8	34.8	31	45	34-44
PG-N63	71.4	63.8	19.8	8.8	41.4	41.6	55	42-54