

Free-To-Air Digital Satellite TV Reception Equipment

SRF011

REF. 4084

SRF112

REF. 4062



Data Sheet



www.ikusi.com

- Satellite TV reception.
- Digital-to-Analogue Transmodulation Process (QPSK → AM) that presents the clear TV programmes transmitted in QPSK Sat-TV channels on conventional VHF/UHF channels.

		SRF-011	SRF-112
Output TV Spectrum		VSB (Vestigial Side Band)	
Remote mode		No	Yes
Output channel TV system		B/G/D/K/I/L	B/G
Output channel audio system		Mono*	A2
Output channel colour system		PAL, SECAM, NTSC	
Output channel selectable between	MHz	45 – 862	
Input Section (QPSK)			
Input frequencies band	MHz	950 – 2150	
Input level	dBm	-65 – -25	
Input loop-through gain	dB	0 (±1)	
AFC Pull-range	MHz	±5	
Symbol rate	MS/s	2 – 45	
MPEG-2 Decoding Section			
Video processing	Main Profile @ Main level		
Audio processing	Layer II		
Teletext - Subtitles Insertion	Yes		
Image Format Conversion	16:9 to 4:3 Pan&Scan and 16:9 to 4:3 Letter-box		
External Video/Audio Loop			
Video and audio L/R output levels	Vpp	–	1,0 (video), 0 – 2,0 (audio)
Vuideo and audio L/R input levels	Vpp	–	0,9 – 1,1 (video), 0,5 – 1,0 (audio)
Video/Audio remodulation Section			
Adjustable video modulation depth	%	80 – 90	
Adjustable audio peak deviation	kHz	±10 – ±50 (except System L)	
Adjustable audio modulation depth	%	10 – 80 (System L)	

* When selecting a stereo audio service, the output channel sound carrier is modulated with the "L+R" sum. If the audio service selected is dual, the carrier can be modulated with any of the "audio1", "audio2" or "audio1+audio2" signals.



Output Section (TV Channel)


Adjustable output level	dB μ V	65 – 80	
Carrier level ratio	dB	12/16 (Mono; A2:Audio1), 20 (A2: Audio2)	
Group delay precorrection		–	Yes
Weighted SNR	dB	> 60	
Spurious in band	dBc	< -58	< -60
Broadband noise ($\Delta B=5$ MHz)	dBc	< -75	

General

Supply Voltage	Vdc	+12	
Consumption	mA	540	590
Operating temperature	°C	0 – +45	
Input RF connector type		(2x) female F	
Output RF connector type		(2x) female F	
DC connector type		banana socket	
Programming interface		RS-232/DB-9	
Video/Audio loop connector type		–	mini-DIN (6 way)
IKUSUP bus connector		–	(2x) 4-pin socket
Dimensions	mm	230 x 195 x 32	

Each module is packed with:

- 2 F plug bridges, 64 mm length, for input tap line and output coupling line.
- 1 DC plug bridge, 53 mm length, for connection of +12 Vdc voltage.



— Example of SRF headend for eight clear digital satellite TV programmes.

SRF HEADENDS

- Satellite TV reception, standard DVB-S / MPEG-2 (EN 300 421).
- Digital-to-Analogue Transmodulation Process (QPSK → AM) that presents the clear TV programmes transmitted in QPSK Sat-TV channels on conventional VHF/UHF channels (VSB vestigial side band or DSB double side band; any TV system and Colour system).
- An SRF headend includes:
 - As many SRF Receiving Modules as free-to-air TV programmes to be distributed.
 - One HPA Amplifier that amplifies the sum of the combined output TV channels from the receivers.
 - One or more CFP Power Supplies.
 - One or more Rack-Frames or wall-fixing Base-Plates. The base-plates can be joined horizontally.
 - Usually, housing units for the base-plates.
 - If the headend is large, one or more AMX-400 combiners.

The SRF headends provide a TV multichannel signal whose level is appropriate to feed the distribution network. With a SRF installed in the headend, the end user does not require a Set Top Box or any additional devices to view the clear digital TV programs being distributed. An extension input at the HPA amplifier allows easy coupling of the wideband 47-862 MHz signal provided by another existing headend.

FUNCTIONAL DESCRIPTION OF THE SRF RECEIVERS

An SRF receiving module carries out the complete channel processing from the input to the output:

- tunes a QPSK Sat-IF digital channel in the 950-2150 MHz band,
- selects a TV programme from the multiplex received, and
- directs it to a conventional TV channel which is selectable throughout the 45-862 MHz band.

Range includes different models for VSB or DSB output channel spectrums; for B/G, D/K, I, L or M/N TV systems; and for mono or A2 stereo/dual sounds.

Programming of each module involves the following selections and settings:

- Central Input Frequency (1 MHz steps).
- Input Symbol Rate (0.001 MS/s steps).
- TV Programme and Audio Service. (Or a Radio Programme. Image will be black).
- Parameters of the output TV channel (video carrier frequency, TV system, colour system, video modulation depth, audio modulation index, carrier level ratio, output level).
- Image Format. Possible conversions are 16:9 to 4:3 Pan&Scan and 16:9 to 4:3 Letter-Box.

Models featuring VSB output are utilizable for adjacent channel operation. If this operation is not required, existing model featuring DSB output may be used without problems. The first ones present, on the other hand, a very low broadband noise floor (< -75 dBc) that permit to use multiple modules in the headend with very little deterioration of the CNR.

SIMPLE CABLING OF THE SRF HEADENDS

The SRF receiving modules feature two directionally coupled input and output ports. Sat-IF signal can therefore be directly fed into the input port of the first module, which in turn passes it through the coupler to the next and so forth. On the output side, the same procedure is repeated which forms the channel coupling. The sum of the combined channels is then connected in the same way to the drive amplifier – the HPA module or an external wideband amplifier – which then feeds the distribution network. For power connection, each module has two DC banana sockets that allow to build a +12 VDC cascade. A third banana socket is available to connect the power for the attached LNB.

An external video/audio loop, which is switched under control software, is available on models SRF-1xx. The loop is not available in the so called economical models (SRF-0xx).

Local programming is carried out with the SPI-300 unit, which is connected to each module individually. Remote programming is possible only if an HMS control unit is installed in the headend. The SRF-0xx economical models do not have IKUSUP sockets and cannot therefore be programmed remotely.