

Specification:		Model: APM-J012-WS
Image Sensor	Image Sensor	1/4" Color CMOS Sensor
	Display Resolution	640 x 480 Pixels(300k Pixels)
	Lens	f. 6 mm, F:2.0 (IR Lens) (3.6mm lens optional)
	Mini. Illumination	0.5Lux
Lens	Lens Type	Glass Lens
	Viewing Angle	60 Degree (3.6mm lens is 90Degree)
Audio	Input	Built-in Microphone
	Output	1 channel audio output
	Audio Compression	ADPCM
Video	Image Compression	MJPEG
	Image Frame Rate	15fps(VGA),30fps(QVGA)
	Resolution	640 x 480(VGA), 320 x 240(QVGA)
	Flip Mirror Images	Vertical / Horizontal
	Light Frequency	50Hz, 60Hz or Outdoor
	Video Parameters	Brightness, Contrast
Communication	Ethernet Interface	Build in 10/100Mbps,Auto MDI/MDIX , RJ-45
	Supported Protocol	HTTP,FTP,TCP/IP, UDP, SMTP, DHCP, PPPoE, DDNS, UPnP, GPRS
	Wireless Standard	IEEE 802.11b/g
	Data Rate	802.11b: 11Mbps (Max.), 802.11g: 54Mbps (Max.)
	Wireless Security	WEP & WPA WPA2 Encryption
Physical	Infrared Light	10 IR LEDs, Night visibility up to 10 meters
	Alarm Input	1 Channel on/of, f Input
	Alarm Output	1 Channel relay Output
	Dimension	80(L) x44(W) x80mm(H)
	Gross Weight	App. 600g
	Color Box	180 x 120 x 160 mm
	Net Weight	App. 400g (accessories included)
Power	Power Supply	DC 5V/2.0A (EU,US,AU adapter or other types optional)
	Power Consumption	5 Watts (Max.)
Environment	Operate Temper.	0° ~ 55°C (14°F ~ 131°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temper.	-10°C ~ 60° (14°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
PC System Requirements	CPU	2.0GHZ or above (suggested 3.0GHz)
	Memory Size	256MB or above (suggested 1.0GHz)
	Display Card	64M or above
	Supported OS	Microsoft Windows 2000/XP/Vista/7
	Browser	IE6.0/7.0/8.0/Firefox/Safari/Google chrome or other standard browsers
Certification	CE, FCC, RoHS	
Warranty	Limited 1-year warranty	

Packing Details:

Model Number	Carton Size	Number/Carton	Picture of Packing
APM-J012-WS	192 x 120 x 170 mm	1pc / Carton	picture as below
	225 x 192 x 170 mm	2pcs / Carton	
	435 x 192 x 170 mm	4pcs / Carton	
	540 x 192 x 170 mm	5pcs / Carton	
	540 x 192 x 330 mm	10pcs / Carton	
	540 x 192 x 485 mm	15pcs / Carton	
	540 x 370 x 330 mm	20pcs / Carton	

Packing List

 CD-Driver	 Network Cable	 Adapter
 APM-J012-WS APM-J012	 User manual	 Accessories

155mm
170mm
105mm

L170*W105*H155mm

User Interface:

The screenshot shows the web interface for an Apexis Network Camera. At the top, there is a green header with the text "Network Camera" and the Apexis logo. Below the header is a navigation bar with buttons for "Live Video", "play", "stop", "snapshot", "record", "audio", and "talk". On the left side, there is a vertical menu with options: "Multi-Device", "Net work", "Audio video", "system", and "other". The main content area is divided into four video feeds: a family sitting on a sofa, a living room with a brown sofa, a bathroom with a sink and toilet, and a close-up of a potted plant. On the left side of the main area, there are controls for "Rate" (set to Full-Speed), "resolution" (640*480), "mode" (50 HZ), "bright" (6), and "contrast" (4). A "default all" button is located below these controls.