



FABBRICA CAVI - ANTENNE - ACCESSORI TV



RF 200 LTA

DOUBLE SCREENED 50 OHM
RF COAXIAL CABLE

Class CPR **E_{ca}**

CU PEE LTA CS PVC2
ø 1,13 mm ø 2,95 mm ø 3,05 mm ø 3,50 mm ø 5,00 mm



| A | B | C | D | E |

MECHANICAL DATA

A	INNER CONDUCTOR	PLAIN COPPER		ø 1,13 mm
B	DIELECTRIC	FOAM POLYETHYLENE		ø 2,95 ± 0,10 mm
C	SHIELD	ALUMINIUM + POLYESTER + ALUMINIUM TAPE		h. 12 mm
		- COVERAGE		100%
D	BRAID	TINNED COPPER		112 x 0,12 mm
		- COVERAGE		90%
E	SHEATH	NON-CONTAMINATING POLYVINYL-CHLORIDE		ø 5,00 ± 0,10 mm
	- COLOUR	## METER ## RF 200 LTA 50 OHM LOW LOSS CABLE		1,13 / 2,95 / 5,00
	- PRINTING	MADE IN ITALY CE 56 WEEK/YEAR EN 50575:2014 + A1:2016 Eca		

MINIMUM BENDING RADIUS (mm)

- **SINGLE** ø EXTERNAL X 5
- **REPEATED** ø EXTERNAL X 10

TEMPERATURE RANGE -30 °C / +70 °C

CABLE WEIGHT (Kg/Km)

- **COPPER** 21,1
- **PLASTIC** 17,8
- **TOTAL** 39,9

ELECTRICAL PROPERTIES at 20°C

IMPEDANCE 50 ± 3 Ohm

CAPACITANCE 80 pF/m

VELOCITY RATIO 80%

RESISTANCE

- **INNER CONDUCT.** 17,2 Ohm/Km
- **BRAID** 13,0 Ohm/Km

TENSION

- **SHEATH SPARK TESTING** 3,5 kV

ATTENUATIONS dB/100 m.

		dB	W
5	MHz	2,6	2263
10	MHz	3,5	1600
50	MHz	7,5	716
100	MHz	10,3	506
200	MHz	14,1	358
400	MHz	20,2	253

MAX. POWER RATING W

		dB	W
500	MHz	22,9	226
600	MHz	25,2	207
800	MHz	29,5	179
1000	MHz	33,4	160
1350	MHz	39,8	138
1500	MHz	42,0	131

		dB	W
1750	MHz	45,8	121
2150	MHz	51,0	109
2250	MHz	51,9	107
2500	MHz	55,2	101
2750	MHz	58,1	96
3000	MHz	60,8	92

STRUCTURAL RETURN LOSS dB

30 ÷ 300	MHz	>27	1000 ÷ 2000	MHz	>17
300 ÷ 600	MHz	>24	2000 ÷ 3000	MHz	>16
600 ÷ 1000	MHz	>18	 ÷	MHz	-

SCREENING EFFECTIVENESS dB

100 ÷ 900	MHz	>85
900 ÷ 2000	MHz	>75
2000 ÷ 3000	MHz	>65

The producer reserves himself to make modification on the item without any notice.