

DETAIL

Model No.	500VA/300W	1000VA/600W	1500VA/900W	2000VA/1200W	3000VA/1800W	5000VA/3000W	8000VA/4800W	10000VA/6000W
Technology	CPU based Digital Circuit + Servo Motor							
INPUT	Voltage Range	140V~250V AC / 80V~140V AC						
	Frequency	50/60Hz						
OUTPUT	Voltage Range	AC 220V / AC 110V						
	Precision	±1%/±3%(Servo Type) / ±10%(Relay Type)						
Efficiency	98%							
Phase	Single Phase							
Status Display	Input Voltage, Output Voltage(Meter)/Input Voltage, Output Voltage, Delay Time(Digital)							
Protection	High Voltage Protection	Yes						
	Overload Protection	Yes						
	Circuit Protection	Fuse / Circuit Breaker						
Delay Time	3~6 Seconds / 2~3 Minutes(Meter) / 6/120Seconds(Digital)							
Safety Standards	CE, EN60950, EN55024							
Operating Conditions	Operating Temperature	0°C~40°C						
	Storage Temperature	-15°C~45°C						
	Relative Humidity	10%RH ~ 95%RH, Non-condensing						
Measurement (mm,H x W x D)	160*115*235	170*125*250	187*145*265	187*145*265	265*220*370	265*220*370	265*220*420	265*220*420
Net Weight(Kg)	2.60	4.80	5.30	6.10	12.50	15.40	27.00	30.00