

DETAIL

Model No.		500VA/300W	1000VA/600W	1500VA/900W	2000VA/1200W	3000VA/1800W	5000VA/3000W	8000VA/4800W	10000VA/6000W
Technology		CPU based Digital Circuit + Servo Motor							
INPUT	Voltage Range	140V~250V AC / 80V~140V AC							
	Frequency	50/60Hz							
OUTPUT	Voltage Range	AC 220V / AC 110V							
	Precision	±1%/±3%(Servo Type) / ±10%(Relay Type)							
Efficiency		98%							
Phase		Single Phase							
Status Display		Input Voltage, Output Voltage(Meter)/Input Voltage, Output Voltage, Delay Time(Digital)							
Protection	High Voltage Protection	Yes							
	Overload Protection	Yes							
	Circuit Protection	Fuse / Circuit Breaker							
Delay Time		3~6 Seconds / 2~3 Minutes(Meter) / 6/120Seconds(Digital)							
Safety Standards		CE, EN60950, EN55024							
Operating Conditions	Operating Temperature	0°C~40°C							
	Storage Temperature	-15°C~45°C							
	Relative Humidity	10%RH ~ 95%RH, Non-condensing							
Measurement (mm,H x W x D)		/	197*145*265	197*145*265	197*145*265	265*220*370	265*220*370	265*220*420	265*220*420
Net Weight(Kg)		/	4.70	5.20	5.80	12.50	15.40	27.00	30.00