

DETAIL

| Model No. | 500VA/300W | 1000VA/600W | 1500VA/900W | 2000VA/1200W | 3000VA/1800W | 5000VA/3000W | 8000VA/4800W | 10000VA/6000W |
|----------------------------|---|--|-------------|--------------|--------------|--------------|--------------|---------------|
| Technology | CPU based Digital Circuit + Servo Motor | | | | | | | |
| INPUT | Voltage Range | 140V~250V AC / 80V~140V AC | | | | | | |
| | Frequency | 50/60Hz | | | | | | |
| OUTPUT | Voltage Range | AC 220V / AC 110V | | | | | | |
| | Precision | ±1%/±3%(Servo Type) / ±10%(Relay Type) | | | | | | |
| Efficiency | 98% | | | | | | | |
| Phase | Single Phase | | | | | | | |
| Status Display | Input Voltage, Output Voltage(Meter)/Input Voltage, Output Voltage, Delay Time(Digital) | | | | | | | |
| Protection | High Voltage Protection | Yes | | | | | | |
| | Overload Protection | Yes | | | | | | |
| | Circuit Protection | Fuse / Circuit Breaker | | | | | | |
| Delay Time | 3~6 Seconds / 2~3 Minutes(Meter) / 6/120Seconds(Digital) | | | | | | | |
| Safety Standards | CE, EN60950, EN55024 | | | | | | | |
| Operating Conditions | Operating Temperature | 0°C~40°C | | | | | | |
| | Storage Temperature | -15°C~45°C | | | | | | |
| | Relative Humidity | 10%RH ~ 95%RH, Non-condensing | | | | | | |
| Measurement (mm,H x W x D) | 160*115*235 | 170*125*250 | 187*145*265 | 187*145*265 | 265*220*370 | 265*220*370 | 265*220*420 | 265*220*420 |
| Net Weight(Kg) | 2.60 | 4.80 | 5.30 | 6.10 | 12.50 | 15.40 | 27.00 | 30.00 |