

item no. **BNC-5170 Red**

connector type
For cable

BNC MALE COMPRESSION 75Ω

Frequency Range	0.3 - 3000 MHz
Impedance (Nom.)	75 Ω
Amp. Rating	5 A
Shielding Effectiveness	> 115 dB @ 1GHz



Return Loss (IEC 169.1.1)
(RF Analyzer E8357A)

0.3 - 500 MHz	- 34.0 dB
500 - 860 MHz	- 30.7 dB
860 - 1000 MHz	- 26.7 dB
1000 - 1750 MHz	- 23.4 dB
1750 - 2150 MHz	- 21.1 dB
2150 - 3000 MHz	- 19.5 dB

Insertion Loss Max.

0.3 - 500 MHz	< 0.07 dB
500 - 860 MHz	< 0.10 dB
860 - 1000 MHz	< 0.14 dB
1000 - 1750 MHz	< 0.18 dB
1750 - 2150 MHz	< 0.20 dB
2150 - 3000 MHz	< 0.26 dB

Temperature

Installing	- 5° to + 50° C
Operating	- 40° to + 100° C
Storing	- 40° to + 100° C

Inner Conductor

Resistance max. @1 A DC **<1 mOhm**

Max. Tensile Strength

Overall **250 N**

Base Material

Body parts **Brass CuZn 39Pb3 / Zinc**

Inner Conductor

Inner conductor **Brass CuZn 39Pb3**

O-ring

EPDM

Plating

Body parts **Nickel**

Color

RED

Inner conductor **Gold**

Date of release **OCT 13 . 2010**