

Zero Smog 4V

Code No.: T0053660699N




Benefits

- › Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces
- › Electronic filter control with optical and acoustical filter alarm
- › Efficiency test via USB port
- › 4 wheels to allow easy movement of the unit
- › Low noise level
- › 4 kits available
- › The fume extraction unit Zero Smog 4V (ZS 4V) is easy to install and operate. It is designed for use as a small central system. A powerful, maintenance-free turbine provides continuous fume extraction at a maximum air extraction rate of 230 m³/h. With setting constant flow control the adjustable turbine speed avoiding unnecessary waste of suction power and saving energy.

In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables



Preheating plates



Technical Data

Dimensions W x D x H (mm)	345 x 325 x 505
Dimensions W x D x H (Inch)	13.58 x 12.79 x 19.88
Weight (ca) in kg	19
Voltage	220-240 V (50/60 Hz)
Heating output	275 VA
Noise level (distance 1 m) dB(A)	< 48
Max. vacuum	---
Capacity m³/h	230
Pre filter	Pre filter mat class F7
Cartridge Volume Extraction	Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb)
Max. capacity	1-4 workplaces
Interface RS232 (Remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB interface	on
WX compatible	on

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE