


# Quick selection table

## Contactors ... 9 to 85A

Frame size		9A		12A		18A		22A	
<b>3-pole Contactors</b>									
Types	AC coil	GMC-9		GMC-12		GMC-18		GMC-22	
	DC coil	GMD-9		GMD-12		GMD-18		GMD-22	
<b>Ratings / IEC60947-4</b>		kW	A	kW	A	kW	A	kW	A
AC1			<b>25</b>		<b>25</b>		<b>40</b>		<b>40</b>
AC3	200/240V	2.5	11	3.5	13	4.5	18	5.5	22
	<b>380/440V</b>	<b>4</b>	<b>9</b>	<b>5.5</b>	<b>12</b>	<b>7.5</b>	<b>18</b>	<b>11</b>	<b>22</b>
	500/550V	4	7	7.5	12	7.5	13	15	22
	690V	4	5	7.5	9	7.5	9	15	18
<b>Ratings / UL508</b>		hp	A	hp	A	hp	A	hp	A
continuous current			20		25		30		32
single phase	115V	0.5		0.5		1		2	
	230V	1		2		3		3	
three phase	200V	2		3		5		7	
	230V	2		3		5		7.5	
	<b>460V</b>	<b>5</b>		<b>7.5</b>		<b>10</b>		<b>10</b>	
	575V	7.5		10		15		15	
NEMA size		00		00		0		0	

