

Apartment amplifier. ATP series

NEW PRODUCT

1^{er} y 2^o
Dividendo



- Models adapted to the 1st and 2nd Digital Dividend.
- Terrestrial and satellite outputs.
- Gain adjustment potentiometers.
- Return path in ATP190, ATP290 and ATP490 series.
- Power supply extended range (110-240V).
- Mains lead.

MODELS	INPUTS	OUTPUTS
ATP190 series	1 TERR + SAT + VR	1
ATP104 series	4 BI-FM-BII/DAB-UHF	1
ATP200 series	1 VHF-UHF	2
ATP290 series	1 TERR + SAT + VR	2
ATP400 series	1 VHF-UHF	4
ATP490 series	1 TERR + SAT + VR	4

MODEL	REF.	ATP190 series		
ATP190-C69	3588	Frequency range MHz	950 - 2150	47 - 862
ATP190-C60	3589			47 - 790 (1 st dividend)
ATP190-C48	3590			47 - 694 (2 nd dividend)
Inputs				1
Outputs				1
Gain	dB		Sat: >22	Terr: >18
Gain adjustment	dB		-	Terr: >10
Output level	dBuV		Sat: 118	Terr: 110
Return path frequency	MHz		5 - 30	
Noise figure	dB		<7	
Mains supply voltage	VAC		100 - 240	
DC transit			Yes	
Consumption	W		<3	
Dimensions	mm		135 x70 x30	

MODELO	REF.	Serie ATP490		
ATP490-C69	3597	Frequency range MHz	950 - 2150	47 - 862
ATP490-C60	3598			47 - 790 (1 st dividend)
ATP490-C48	3599			47 - 694 (2 nd dividend)
Inputs				1
Outputs				4
Gain	dB		Sat: >22	Terr: >18
Gain adjustment	dB		-	Terr: >10
Output level	dBuV		Sat: 113	Terr: 103
Return path frequency	MHz		5 - 30	
Noise figure	dB		<7	
Mains supply voltage	VAC		100 - 240	
DC transit			Yes (on an output)	
Consumption	W		<3	
Dimensions	mm		135 x70 x30	

MODEL	REF.	ATP400 series		
ATP400-C69	3594	Frequency range MHz		47 - 862
ATP400-C60	3595			47 - 790 (1 st dividend)
ATP400-C48	3596			47 - 694 (2 nd dividend)
Inputs				1
Outputs				4
Gain	dB		22	
Gain adjustment	dB		15	
Output level	dBuV		>103	
Noise figure	dB		<4	
Mains supply voltage	VAC		100 - 240	
Consumption	W		<3	
Dimensions	mm		135 x70 x30	

MODEL	REF.	ATP104 series				
ATP104-C69	3585	Frequency range MHz	45 - 68	88 - 108	174 - 240	47 - 862
ATP104-C60	3586					47 - 790 (1 st div.)
ATP104-C48	3587					47 - 694 (2 nd div.)
Inputs			1 BI	1 FM	1 BIII/DAB	1 UHF
Outputs			1			
Gain		dB	>31			
Gain adjustment		dB	>15			
Output level		dBµV	106			
Noise figure		dB	<4			
Mains supply voltage		Vac	100 - 240			
Consumption		W	<3			
Dimensions		mm	135 x70 x30			