

Apartment amplifier. ATP series

NEWPRODUCT

1er y 2º
Dividendo



- Models adapted to the 1st and 2nd Digital Dividend.
- Terrestrial and satellite outputs.
- Gain adjustment potentiometers.
- Return path in ATP190, ATP290 and ATP490 series.
- Power supply extended range (110-240V).
- Mains lead.

MODEL	REF.	Serie ATP200	
ATP200-C69	3583	Frequency range MHz	47 - 862
ATP200-C60	3434		47 - 790 (1 st dividend)
ATP200-C48	3584		47 - 694 (2 nd dividend)
Inputs			1
Outputs			2
Gain	dB		25
Gain adjustment	dB		15
Output level	dBµV		103
Noise figure	dB		<4
Mains supply voltage	VAC		100 - 240
Consumption	W		<1,5
Dimensions	mm		90 x 58 x 27

MODEL	REF.	Serie ATP290		
ATP290-C69	3591	Frequency range MHz	950 - 2150	47 - 862
ATP290-C60	3592			47 - 790 (1 st dividend)
ATP290-C48	3593			47 - 694 (2 nd dividend)
Inputs				1
Outputs				2
Gain	dB		Sat: >22	Terr: >18
Gain adjustment	dB		-	Terr: >10
Output level	dBµV		Sat: 116	Terr: 106
Return path frequency	MHz			5 - 30
Noise figure	dB			<7
Mains supply voltage	VAC			100 - 240
DC transit				Yes (on an output)
Consumption	W			<3
Dimensions	mm			135 x70 x30