


Product Image



Product Dimensions



Characteristics

Nominal Voltage		12V
Nominal Capacity (10 hour rate)		42Ah
Capacity 25°C(77°F)	20 hour rate (2.33A)	46.6Ah
	5 hour rate (7.7A)	38.5Ah
	1 hour rate (27.9A)	27.9Ah
Internal Resistance	Full Charged Battery 25°C	≤9mΩ
Capacity affected by Temperature (10 hour)	40°C (104°F)	102%
	25°C (77°F)	100%
	0°C (32°F)	85%
	-15°C (5°F)	65%
Self-Discharge 25°C(77°F) Capacity	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Constant Voltage) 25°C (77°F)	Float	Initial Charging Current Less than 10.5A Voltage 13.6-13.8V
	Cycle	Initial Charging Current Less than 10.5A Voltage 14.4-14.9V

Packaging

Battery Dimensions	Length	198mm
	Width	166mm
	Height	172mm
	Total Height	172mm
Box Dimensions	Length	213mm
	Width	179mm
	Height	211mm
Quantity Per Box		1 PC per box
Net weight Per Cell		12.9 kg±100g
Net weight Per Box		12.9kg
Gross Weight		13.4kg

Discharge Constant Current per Cell (Amperes at 77°F25°C)







F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	141.2	94.1	70.9	44.1	31.7	27.9	17.0	12.5	8.0	4.9	4.37	2.42
1.65V	130.2	86.7	68.0	42.9	30.8	27.2	16.7	12.2	7.9	4.8	4.33	2.40
1.70V	132.4	88.2	65.0	41.8	30.0	26.4	16.4	12.0	7.8	4.8	4.28	2.38
1.75V	117.0	77.9	62.0	40.6	29.1	25.7	16.0	11.7	7.7	4.8	4.24	2.35
1.80V	110.3	73.5	59.1	39.4	28.3	24.9	15.6	11.4	7.6	4.7	4.20	2.33

Discharge Constant Power per Cell (Watts at 77°F 25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	263.4	175.5	132.3	82.3	59.0	52.1	31.8	23.2	14.9	9.1	8.1	4.5
1.65V	242.8	161.8	126.7	80.1	57.5	50.7	31.2	22.8	14.7	9.0	8.1	4.5
1.70V	246.9	164.5	121.2	77.9	55.9	49.3	30.6	22.4	14.5	8.9	8.0	4.4
1.75V	218.1	145.3	115.7	75.7	54.3	47.9	29.9	21.8	14.3	8.9	7.9	4.4
1.80V	205.8	137.1	110.2	73.5	52.7	46.5	29.1	21.3	14.1	8.8	7.8	4.3

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice.

Performance Characteristics



Battery Construction

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Si-Rubber	Copper	Fiberglass	Sulfuric acid