



- Preheat plate
- 600 W, 230 V
- Board size upto 120 x 190 mm
- Temperature range 50 °C - 400 °C
- Digital display for set and actual temperature
- 3 Infrared high temperature ceramic elements for fast and efficient heat up
- 2 heated zones can be selected
- External sensor (accessory) connectable
- RS 232-Interface cable e.g. for connection to WHA 3000 hot air station
- Easy Fix board holder
- K-type thermo couple socket for monitoring

### WHP 3000 Infrared preheating plate

Product no.: T0053338699N

|  |                                    |
|--|------------------------------------|
| Dimensions L x W x H (mm)                      | 254 x 395 x 70 mm                  |
| Dimensions L x W x H (inches)                  | 10 x 15.55 x 2.76 Inch             |
| Weight (approx.) in kg                         | ---                                |
| Voltage  | 230 V, 50/60 Hz                    |
| Power  | 600 W                              |
| Channels                                       | ---                                |
| Temperature range (depends on tool) °C         | ---                                |
| Temperature range (depends on tool) °F         | ---                                |
| Temperature accuracy °C                        | ---                                |
| Temperature accuracy °F                        | ---                                |
| Temperature accuracy for hot air °C            | ---                                |
| Temperature accuracy for hot air °F            | ---                                |
| Temperature stability °C                       | ---                                |
| Temperature stability °F                       | ---                                |
| Equipotential bonding socket                   | ---                                |
| Display  | ---                                |
| Additional vacuum pump                         | ---                                |
| Max. hot air flow rate l/min (depends on tool) | ---                                |
| Capacity l/min                                 | ---                                |
| Max. vacuum                                    | ---                                |
| Interface                                      | 1 x RS232, 1 x thermocouple type K |