

ALTAVOCES EXPONENCIALES SERIE AC-600

AC-615T

15 W **119 dB**

AC-630T

30 W **121 dB**

AC-650T

50 W **133 dB**

Altavoces exponenciales de boca circular fabricados en aluminio y acero para línea de 100 V y con toma de baja de impedancia (8 ohm).

IP66

AC-615T



AC-650T



AC-630T



	AC-615T	AC-630T	AC-650T
Potencia RMS	15 W	30 W	50 W
Selección de potencia	15, 7,5, 3,75 y 1,9 W 8 ohm	30, 15, 7,5 y 3,8 W 8 ohm	50, 25, 12,5 y 6,25 8 ohm
SPL 1 m, 1 kHz	107 dB (1 W) / 119 dB (15 W)	109 dB (1 W) / 121 dB (30 W)	117 dB (1 W) / 133 dB (50 W)
Respuesta en frecuencia	300 ~ 10.000 Hz	380 ~ 10.000 Hz	380 ~ 6.500 Hz
Grado de protección	IP66 (IEC-529)	IP66 (IEC-529)	IP66 (IEC-529)
Dimensiones (mm)	Ø 207 x 245	Ø 246 x 292	Ø 327 x 350
Peso	1,3 kg	2,1 kg	2,8 kg
Acabado	aluminio y acero	aluminio y acero	aluminio y acero



EXPONENTIAL LOUDSPEAKERS SERIES AC-600

AC-615T

15 W

119 dB

AC-630T

30 W

121 dB

AC-650T

50 W

133 dB

Exponential loudspeakers with a circular mouth made in aluminium and steel. 100 V line and low impedance connection (8 ohm).

IP66

AC-615T



AC-650T



AC-630T



	AC-615T	AC-630T	AC-650T
RMS power	15 W	30 W	50 W
Power selection	15, 7.5, 3.75 & 1.9 W 8 ohm	30, 15, 7.5 & 3.8 W 8 ohm	50, 25, 12.5 & 6.25 8 ohm
SPL 1 m, 1 kHz	107 dB (1 W) / 119 dB (15 W)	109 dB (1 W) / 121 dB (30 W)	117 dB (1 W) / 133 dB (50 W)
Frequency response	300 ~ 10.000 Hz	380 ~ 10.000 Hz	380 ~ 6.500 Hz
Protection	IP66 (IEC-529)	IP66 (IEC-529)	IP66 (IEC-529)
Dimensions (mm)	Ø 207 x 245	Ø 246 x 292	Ø 327 x 350
Weight	1.3 kg	2.1 kg	2.8 kg
Finish	aluminium and steel	aluminium and steel	aluminium and steel

