

SWAN C-CAM Camera Module



Κύρια χαρακτηριστικά κάμερας

- Λειτουργία 4 σε 1 (TVI, AHD, CVI, CVBS).
- Αισθητήριο 2704 (H) x 2104 (V), approx. 5.69 MP.
- DNR (Digital Noise Reduction: 3D & 2D).
- Τάση λειτουργίας από 7VDC έως 25VDC.
- D-WDR (Digital Wide Dynamic Range).
- Μενού μέσω Pelco-C (Coaxitron) ή τοπικά.
- Προστασία από ανάστροφη τροφοδοσία μέχρι 40VDC.
- Μικρόφωνο υψηλής ευαισθησίας.
- Διαστάσεις: 32χιλ x 32χιλ.



Τεχνικά χαρακτηριστικά

Image Device	1/2.8" 5.69 MP SONY CMOS (Exmor-R STARVIS)
Scanning system	Progressive scan
Resolution	TVI: 4MP 25/30FPS AHD: 4MP 25/30FPS CVI: 4MP 25/30FPS CVBS: 960H
Total Pixels	2704 (H) x 2104 (V)
Effective Pixels	2616 (H) x 1964 (V)
Shutter Speed	Auto / Manual (1/30(1/25) ~ 1/60000) / Flicker
Day & Night	Auto / COLOR / B&W / EXT
White Balance	Auto / Auto Ext / Preset / Manual
Mirror	Off / H / V / H&V
DNR (3D + 2D)	Off / Low / Middle / High
Privacy	Off / On (16 points)
Motion	Off / On (16 points)
Shading	0 - 100%
D-WDR / BLC / HLC	Off / D-WDR / BLC
OSD	OSD Control Switch Built in and over Coaxitron protocol
Language	ENG, GER, FRA, ITA, SPA, POL, RUS, POR, NED, TUR
Video Output	AHD / TVI / CVI / CVBS
Lens	4,3mm Pinhole Lens
Power	DC 7V~25V
Power Consumption	120mA