

Transformer testing

MI 3280 Digital Transformer Analyser



The MI 3280 Digital Transformer Analyser is a portable, battery (Li-ion) powered test instrument intended for diagnosing of turn ratio, phase deviation, excitation current and winding resistance of single and three phase transformers. It has an excellent IP protection: IP65 (case closed), IP54 (case open) allowing the use of the instrument in harsh environments. The operation is straightforward and clear to enable the user to operate the instrument without the need for special training. For advanced users the AUTO SEQUENCES and visual tests are available.

High Voltage Insulation / Continuity / Earth

MEASURING FUNCTIONS

Available functions and features offered by the Digital Transformer Analyser:

- Turn ratio measurement of single and three phase transformers;
- Phase deviation between high voltage and low voltage winding;
- Excitation current;
- Winding resistance measurement of single and three phase transformers (Power Transformers up to 1,6 MVA).

KEY FEATURES

- A 4.3" color LCD display with touch screen offers easy-to-read results and all associated parameters.
- The operation is straightforward and clear to enable the user to operate the instrument without the need for special training.
- Test results can be stored on the instrument.

- PC software that is supplied as a part of standard set enables transfer of measured results to PC where they can be analysed or printed.
- Built-in help screens for referencing on site.
- Autotest sequences.
- Built-in charger and rechargeable batteries as standard accessory.
- BT communication with PC, Android tablets and smart phones via built-in BT.
- PC SW Metrel ES Manager for creation of test structures and uploading, downloading of test results, autotest editor and report creation.
- High degree of protection IP 65 (case closed), IP 54 (case open).

APPLICATION

- Three phase and single phase power transformers.
- Voltage transformers.
- Current transformers.

STANDARDS

Functionality

- C57.12.70
- IEC 60076-1

Electromagnetic compatibility

- EN 61326

Safety

- EN 61010 - 1
- EN 61010 - 2 - 030
- EN 61010 - 2 - 033
- EN 61010 - 031

Li-ion battery pack

- IEC 62133

TECHNICAL SPECIFICATION

Function	Measuring range	Resolution	Accuracy		
TURN RATIO <i>r, rA, rB, rC</i>	Excitation voltage 80 V	0.8000 ... 9.9999	0.0001	±(0.2% of reading + 2 digits)	
		10.000 ... 99.999	0.001	±(0.2% of reading + 2 digits)	
		100.00 ... 999.99	0.01	±(0.2% of reading + 2 digits)	
		1000.0 ... 1999.9	0.1	±(0.5% of reading + 2 digits)	
		2000.0 ... 3999.9	0.1	±(0.5% of reading + 2 digits)	
	Excitation voltage 40 V	0.8000 ... 9.9999	0.0001	±(0.2% of reading + 2 digits)	
		10.000 ... 99.999	0.001	±(0.2% of reading + 2 digits)	
		100.00 ... 999.99	0.01	±(0.2% of reading + 2 digits)	
		1000.0 ... 1999.9	0.01	±(0.5% of reading + 2 digits)	
		2000.0 ... 3999.9	0.1	±(0.5% of reading + 2 digits)	
	Excitation voltage 10 V	4000.0 ... 8000.0	0.1	±(1.0% of reading + 2 digits)	
		0.8000 ... 9.9999	0.0001	±(0.2% of reading + 2 digits)	
		10.000 ... 99.999	0.001	±(0.2% of reading + 2 digits)	
		100.00 ... 999.99	0.01	±(0.5% of reading + 2 digits)	
		1000.0 ... 8000.0	0.1	n/a	
	Excitation voltage 5 V	0.8000 ... 9.9999	0.0001	±(0.2% of reading + 2 digits)	
10.000 ... 99.999		0.001	±(0.2% of reading + 2 digits)		
100.00 ... 999.99		0.01	±(0.5% of reading + 2 digits)		
1000.0 ... 8000.0		0.1	n/a		
Excitation voltage 1 V		0.8000 ... 9.9999	0.0001	±(0.2% of reading + 2 digits)	
EXCITATION CURRENT <i>i, iA, iB, iC</i>	Test frequency 55, 65 or 70 Hz	10.000 ... 99.999	0.001	±(0.5% of reading + 2 digits)	
		100.00 ... 999.99	0.01	n/a	
		1000.0 ... 8000.0	0.1	n/a	
		0.10 mA ... 9.99 mA	0.01 mA	±(2 % of reading + 0.20 mA)	
		10.0 mA ... 99.9 mA	0.1 mA	±(2 % of reading + 2 digits)	
PHASE DEVIATION <i>fi, jA, jB, jC</i>	Test frequency 55, 65 or 70 Hz	100 mA ... 999 mA	1 mA	±(2 % of reading + 2 digits)	
		1.00 A ... 1.10 A	0.01 A	±(2 % of reading + 2 digits)	
		1.0 mΩ ... 999.0 mΩ	0.1 mΩ	±(2 % of reading + 3 digits)	
		1.000 Ω ... 9.999 Ω	0.001 Ω	±(2 % of reading + 2 digits)	
		10.00 Ω ... 99.99 Ω	0.01 Ω	±(2 % of reading + 2 digits)	
WINDING RESISTANCE <i>R, RA, RB, RC</i>	Test current 10 mA ... 1000 mA	100.0 Ω ... 999.9 Ω	0.1 Ω	±(2 % of reading + 2 digits)	
		Battery power supply	14.4 V DC (4.4Ah Li-ion)		
		Battery charging time	typical 4.5 h (deep discharge)		
		Mains power supply	90-260 VAC, 45-65 Hz, 100 VA (300 V CAT II)		
		Protection classification	reinforced insulation		
GENERAL	Measuring category	50 V CAT IV			
	Pollution degree	2 			
	Degree of protection	IP 65 (case closed), IP 54 (case open)			
	Dimensions (w x h x d)	360 x 160 x 330 mm			
	Weight	8.8 kg, (with battery and accessories)			

ORDERING INFORMATION



- Instrument MI 3280
- 4 wire test lead with Kelvin clips, 2.5 m 4 pcs
- USB cable
- Mains cable
- Soft carrying bag
- Metrel ES Manager BASIC license*
- Instruction manual
- Calibration certificate

*Metrel ES Manager can be downloaded free of charge from Metrel Web server.

OPTIONAL ACCESSORIES

Photo	Order No.	Acc. description
	A 1615 2M5	Kelvin test lead HO-H1, 2.5 m
	A 1615 5M	Kelvin test lead HO-H1, 5 m
	A 1618 2M5	Kelvin test lead X2-X3, 2.5 m
	A 1618 5M	Kelvin test lead X2-X3, 5 m
	A 1616 2M5	Kelvin test lead H2-H3, 2.5 m
	A 1616 5M	Kelvin test lead H2-H3, 5 m
	A 1617 2M5	Kelvin test lead X0-X1, 2.5 m
	A 1617 5M	Kelvin test lead X0-X1, 5 m

METREL D.D.

Measuring and Regulation Equipment Manufacturer
Ljubljanska 77, SI-1354 Horjul, Slovenia
T +386 (0)1 75 58 200, F +386 (0)1 75 49 226
metrel@metrel.si, www.metrel.si

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery.
Subject to technical change without notice.