

Zero Smog 6V

Product no.: T0053666699N



Benefits

- › Equipped with HEPA H13 particle filter and Fine dust pre-filter F7
- › The Constant Flow Control (CFC) guarantees optimal air flow regulation for each working place independent of the connected workplaces
- › 3 operating modes: Standard Speed Control: Selected by the user irrespective of the load on the system, Speed Limiting Control: The speed is automatically varied to match the load on the system, Economy Control: The rate of fume absorption is maintained at a constant value
- › Electronic filter control with optical and acoustical filter alarm
- › Low noise emission levels for a quiet workspace
- › RS232 port, can be remotely controlled via remote control (optional accessory) or by a PC with RS232 connection
- › Max. blower capacity 615 m³/h
- › Efficiency test via USB port



Technical Data

Dimensions L x W x H (mm)	460 x 460 x 665
Dimensions L x W x H (inches)	18,11 x 18,11 x 26,18
Weight (approx.) in kg	40
Voltage	230 V, 50/60 Hz (120 V, 60 Hz)
Power	460 VA
Noise level (distance 1 m) dB(A)	< 51
Max. vacuum	---
Capacity m ³ /h	615
Pre-filter	Pre filter mat class F7
Compact filter	Particle filter H13, Wide band gas filter (50 % Active carbon / 50 % Chemisorb)
Max. capacity	1-8 workstations
RS232 interface (remote control)	All system functions can be operated and remotely monitored via the RS232 port.
USB port	on
WX-compatible	on