




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.82 – 2.08 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	.3 mm[.012 in]
Product Length	20.32 mm[.8 in]
Compatible Insulation Diameter Range	3.1 – 4.1 mm[.12 – .16 in]
Wire Size	.82 – 2.08 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	500
Packaging Method	Loose Piece/Carton

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 720725-1 DAHT 250 FASTIN-ON TAB REC 18-14 ASSY	TE Part # 1-1579007-4 EXTRACTION TOOL	TE Part # 4-1579007-3 EXTRACTION TOOL KIT	TE Part # 58524-1 PROCRIMPER TOOL & DIE
TE Part # 90165-1 DAHT 250 FASTON REC 18-14 ASSY	TE Part # 42924-2 FF 250 REC 18-14AWG TPBR PRE CRIMPED	TE Part # 58524-2 PROCRIMPER DIE	TE Part # 3-1377175-2 SMP 0-0042238-2


Also in the Series | FASTIN-FASTON 250

Crimp Terminal Housings(210)	Insertion & Extraction Tools(2)	PCB Terminals(2)	Quick Disconnects(251)
-------------------------------------	--	-------------------------	-------------------------------

Customers Also Bought

TE Part #DTM06-6S-E007 PLG, 6P, GRY, N, XCAP	TE Part #180940 FF 250 TAB HSG 3P NYLON NAT	TE Part #180384-2 FF 250 REC 4-6MM2 PTBR LP	TE Part #180924 FF 250 TAB HSG 2P NYLON NAT
---	--	--	--






TE Part #180941
FF 250 REC HSG 3P NYLON NAT



TE Part #DTHD04-1-4P-L013
REC, 1P, BLK, N, SIZE 4, REVERSE FLANGE



TE Part #753787-1
EXTRACTION TOOL FOR MIC MK II

TE Part #D69446-000
TMS-SCE-3/16-9-CS-0016



TE Part #928948-2
FF 250 TAB 1.0-2.5 MM2 TP CUZN30

TE Part #477605-001
SSC-2/U

Documents

Product Drawings

FF 250 REC 18-14AWG TPBR PRE CRIMPED

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_42238-2_AJ_c-42238-2-aj.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_42238-2_AJ_c-42238-2-aj.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_42238-2_AJ_c-42238-2-aj.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

FASTIN_FASTON_Product_Line

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (non U.S.)

42238-2

Receptacle, 18 – 14 AWG Wire Size, .82 – 2.08 mm² Wire Size, Mating Tab Width 6.35 mm [.25 in], Straight, Brass, FASTIN-FASTON 250, Quick Disconnects



Japanese

[Instruction Sheet \(non U.S.\)](#)

Japanese