

HCS-3940D Delegate Unit



Features

- Stylish and ergonomic design
- Smaller, compact and practical, convenient for transportation
- Connection cable is routed from the bottom through the hole in the table for a tidy desktop
- Fully digital audio technology
- Hi-Fi loudspeaker
- Excellent immunity to RF interference from mobile phones
- Supporting "PnP" (plug and play)

The delegate unit meets the basic demands of the conferences. It provides facilities for speaking, registering a request-to-speak and listening. It has excellent immunity to RF interference from mobile phones. The loudspeaker offers superior acoustics with minimal feedback for enhanced intelligibility.

Functions

- Compliant to ISO 22259
- Gain of each microphone adjustable separately, fitting the individual orator's voice to achieve perfect speech pickup any time
- Integrated high-pass filter (low-cut switch) to cut low frequency elements from the audio when needed
- Excellent immunity to RF interference from mobile phones and comparable devices
- Equipped with 5PIN microphone socket, stem microphone ordered separately, suitable for MS5* and MS**E type stem microphone
- Stem microphone can be unplugged during adjournment, easy to maintain
- Hi-Fi loudspeaker, minimal feedback, mutes automatically when microphone is active
- Microphone On/Off button
- Every conference unit is assigned an individual serial number, and its ID can be assigned automatically or manually through conference system

- System when operated in stand-alone mode can implement the following facilities:
 - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time
 - ◆ "OPEN" mode, microphone key with request-to-speak registration (AUTO)
 - ◆ " OVERRIDE" mode, microphone key control with override of the active microphones (FIFO)
 - ◆ "VOICE" mode, microphone activation on speaking
 - ◆ "APPLY" mode, delegate applies to speak by pressing apply key, delegate can speak only when operator or chairman approved his application
 - ◆ "PTT" mode, press microphone On/Off button to talk
- Automatic video tracking, when cooperating with IP camera or video matrix + camera
- Set any delegate unit to be VIP unit
 - ◆ Up to 32 units can be set as VIP in one system by main unit's menu or built-in Web page
 - ◆ VIP unit can be activated as long as the total of active microphones is not beyond 6 (incl. chairman/delegate/VIP unit, except "VOICE" mode)

Controls and Indicators

- Headphone volume up and down buttons
- Microphone On/Off button with indicator

Interconnections

- Socket for pluggable stem microphone
- Ø 3.5 mm stereo headphone jack
- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications

Electrical

Max. consumption 2 W

Headphone connection

Frequency response 40 Hz to 16 kHz

Earphone load impedance ≥16 Ohm

Earphone output 10 mW

Interface data

Connector Ø 3.5 mm stereo jack for headphone

Mechanical

Mounting Tabletop

Dimensions (h x w x d) 66x99x143 mm

Weight 0.9 kg

Color Charcoal gray (PANTONE Cool Gray 11 C) panel
+ black (PANTONE 419 C) base

Ordering Information

- HCS-3940D Compact Digital Conference System
Delegate Unit (tabletop, charcoal gray panel + black base, charcoal gray button, stem microphone to be ordered separately)