

HCS-3940C Chairman Unit



Features

- Stylish and ergonomic design
- Smaller, compact and practical, convenient for transportation
- Connection cable is routed from the bottom through the hole in the table for a tidy desktop
- Fully digital audio technology
- Hi-Fi loudspeaker
- Priority key and Next key
- Excellent immunity to RF interference from mobile phones
- Supporting "PnP" (plug and play)

The stylish and ergonomically designed chairman unit has all the necessary facilities to enable the user to chair a conference. It has excellent immunity to RF interference from mobile phones. Similar in appearance to HCS-3940D Delegate Unit, the HCS-3940C Chairman Unit includes a microphone priority button. When pressed, the priority button causes all currently active delegate microphones to be switched off temporarily or permanently, allowing the chairman to take control of the meeting. The loudspeaker offers superior acoustics with minimal feedback for enhanced intelligibility.

Functions

- Compliant to ISO22259
- Gain of each microphone adjustable separately, fitting the individual orator's voice to achieve perfect speech pickup any time
- Integrated high-pass filter (low-cut switch) to cut low frequency elements from the audio when needed
- Excellent immunity to RF interference from mobile phones and comparable devices
- Equipped with 5PIN microphone socket, stem microphone ordered separately, suitable for MS5* and MS**E type stem microphone
- Stem microphone can be unplugged during adjournment, easy to maintain
- Hi-Fi loudspeaker, minimal feedback, mutes automatically when microphone is active
- Microphone On/Off button
- Every conference unit is assigned an individual serial number, and its ID can be assigned automatically or manually through conference system
- System when operated in stand-alone mode can implement the following facilities:
 - ◆ "ACTIVE MICS", set the number of delegates permitted to speak at the same time
 - ◆ "OPEN" mode, microphone key with request-to-speak registration (AUTO)
 - ◆ "OVERRIDE" mode, microphone key control with override of the active microphones (FIFO)
 - ◆ "VOICE" mode, microphone activation on speaking
 - ◆ "APPLY" mode, delegate applies to speak by pressing apply key, delegate can speak only when operator or chairman approved his application
 - ◆ "PTT" mode, press microphone On/Off button to talk
- Automatic video tracking, when cooperating with IP camera or video matrix + camera
- Activation at any time (if the amount of active microphones in the system is less than 6, except "VOICE" mode)
- Priority key can switch off or mute the speaking units according to preset
- Approves/denies all delegates' speaking requests
- System supports up to 100 chairman units, chairman units have the control facilities listed above (set by main unit's menu or built-in Web page)

Controls and Indicators

- Headphone volume up and down buttons
- Microphone On/Off button with indicator
- Priority key with indicator
- Next key with indicator

Interconnections

- Socket for pluggable stem microphone
- Ø 3.5 mm stereo headphone jack
- 1.5 m cable with 6P-DIN plug
- 0.6 m cable with 6P-DIN socket

Technical Specifications**Electrical**

Max. consumption 2 W

Headphone connection

Frequency response 40 Hz to 16 kHz

Earphone load impedance ≥16 Ohm

Earphone output 10 mW

Interface data

Connector Ø 3.5 mm stereo jack for headphone

Mechanical

Mounting Tabletop

Dimensions (h x w x d) 66x99x143 mm

Weight 0.9 kg

Color Charcoal gray (PANTONE Cool Gray 11 C) panel
+ black (PANTONE 419 C) base

Ordering Information

HCS-3940C Compact Digital Conference System
Chairman Unit (tabletop, charcoal gray
panel + black base, charcoal gray
button, stem microphone to be ordered
separately)